

เครื่องสกัดลม

CHIPPING HAMMERS

Precision valve allows excellent control during air consumption, Durable quick change spring retainer



G10



G16



C6

Model	G10	G16	C6
Impact frequency	$\geq 16\text{Hz}$	$\geq 16\text{Hz}$	$\geq 32\text{Hz}$
Impact energy	$\geq 43\text{J}$	$\geq 55\text{J}$	$\geq 10\text{J}$
Air consumption	$\leq 26\text{L/S}$	$\leq 28\text{L/S}$	$\leq 21\text{L/S}$
Pituitary diameter	38 mm	mm	30 mm
ขนาดสายลม	16 mm	19 mm	13 mm
ขนาดแกนดอกสกัด	24x70 mm	24x70 mm	175x60 mm
It is used or pressure	0.63 Mpa	0.63 Mpa	0.63 Mpa
ความยาวรวม	570 mm	580 mm	365 mm
น้ำหนัก	10 kg	14 kg	6.4 kg
ราคา	3,200	4,500	4,000
เฉพาะดอกสกัด	400	400	400

เครื่องสกัดลม

DEMOLITION TOOL



B47C



B67C



B83C

MODEL	B47C	B67C	B83C
ขนาดลูกสูบ	47.6 mm	50.8 mm	63 mm
Impact energy	$26 \pm 10\% \text{J}$	$37 \pm 10\% \text{J}$	$100 \pm 10\% \text{J}$
Impact Power	$0.67 \pm 10\% \text{Kw}$	$0.9 \pm 10\% \text{Kw}$	$1.8 \pm 10\% \text{Kw}$
Blows frequency	$26 \pm 5\% \text{Hz}$	$24 \pm 5\% \text{Hz}$	$18 \pm 5\% \text{Hz}$
Working Pressure	0.63 Mpa	0.63 Mpa	0.63 Mpa
Air consumption	$28 \pm 15\% \text{L/s}$	$42 \pm 15\% \text{L/s}$	$55 \pm 15\% \text{L/s}$
ขนาดสายลม	19 mm	19 mm	19 mm
ความยาวรวม	550 mm	610 mm	686 mm
น้ำหนัก	21.5 kg	30.0 kg	39.0 kg
ราคา	15,000	24,000	27,300
เฉพาะดอกสกัด	1,000	1,600	1,600